

Land Pride 606NT Compact Drill

Description

Land Pride's 606NT is a 6' Pull-type No-Till Drill and features an end-wheel design that reduces side-loading on openers when operated on contours and curves, eliminating premature opener wear. This time-proven design allows the 606NT to stay on side hills and maintain accuracy going over hills and through valleys. With the optional native grass and small seeds box, this unit is quite capable in pasture renovations and food plot seeding. Other features like heavy-duty coulters, calibration crank, central grease bank, lock-out hubs for transport, and optional weight brackets create a system designed for long-term dependability and productivity in a broad range of seeding applications. 40 HP Min.

Made in the USA



Features and Benefits

Compact Drills

606NT Model

Features	Benefits
Hydraulic depth stop	Provides infinite range of adjustments to tailor coulters to seeding depth.
Choice of 2x13 Single Press Wheel or 3x13 Center Rib Press Wheel	Press wheel options allow tailoring to various soil conditions.
Clevis Style Drawbar Hitch or Pintle Hitch	Allows you to hook up to multiple applications.
2 bu/ft. Box Capacity	Larger box reduces downtime / more acres per fill.
1 3/4" Fluted Seed Cups with Powdered Metal Flutes	Delivers outstanding accuracy.
Calibration Crank	Calibrating your machine will allow you to put on only the amount you desire.
Grease Bank	Lubricate all major components from one location.
4 Speed Gearbox for various seed rates	Makes seed rate changes quick and painless and gives a wider range of adjustment.
Heavy Duty Coil Springs for down pressure on press wheels	Gives you the range from 90 to 180 lbs. of consistent down pressure.
T-Handle Opener Depth Adjustment	Provides 18 different positions for accurate depth.
Walkboard w/Steps	Allows you to refill seed from end to end.
Spring-Steel Coulters Mounting Bars	Takes shock loads better.
Choice of two different coulters	Give you a wide range of penetration and performances.



Rain-Flo Equipment

Model #1800 Plastic Mulch Lifter

Features

- Will lift plastics from 3 ft. to 5 ft. wide with fast and easy adjustments
 - Lifting plows uses Case I.H. 18" right and left hand "Deep-suck" Shares
 - Two spring loaded vine cutting disks
 - Removable center disk to cut plastic in middle
 - Heavy shanks have 5/8" safety shear bolts.
- Auto-reset is optional
- The Challenger is build to last and make your job easier
 - Approximate tractor size: 55 to 100 hp FWD



MS11 Series Manure Spreader

Features

- Heavy-duty paddle beater
- Poly-bonded floor
- Field-installed top beater kits
- Hydraulic conversion kits



Paddle beaters help create a smooth, even finish
 The heavy-duty paddle beater assemblies on the MS11 Series Small Manure Spreaders ensure aggressive shredding action, while the large-diameter beaters deliver greater tip speed for wide, even and chunk-free spread patterns.

Manufacturer	John Deere
Model	MS1112
Capacity	
Heaped, bu m3	125 (4.405)
Struck level, cu. ft m3	75 (2.124)
Liquid, gal. (L)	N/A
Dimensions	
Top of flare width, in. (cm)	54 (137)
Inside width, in. (cm)	48 (122)
Inside length, ft (m)	10.6 (3.2)
Inside depth, in. (cm)	22 (56)
Overall length	---
Horizontal beater configuration, ft, in. (m)	15.3 (465)
Overall width with standard tires, in. (cm)	80 (203)
Overall loading height - top of flare, in. (cm)	43.5 (110)
Weight	
Loaded with base tire, lb (kg)	---
Implement with base tire, lb (kg)	1600 (726)
Towing unit minimum weight, lb (kg)	4,547 (2,062) *
Tongue weight (approximate), lb (kg)	NA
PTO drive	
Standard (rpm)	540
Optional (rpm)	NA
Shear bolt protection	NA
Drive system	
Apron	---
Chain type	67XH
Construction	
Floor	Bonded poly
Box	Corrosion resistant galvanized steel
Set-up time	
Labor hours	.5
Warranty	
Time period	1 year for ag and residential use; 90 days for commercial use
Do not tow more than 1.5 times the towing weight.	
If towed equipment does not have brakes, do not travel more than 32km/hr (20mph).	

BCS Tractors

BCS model 732 is the most economical of the Professional Series, with **more features, more horsepower, and more versatility** than Harvester models.

Differential Drive gives the operator increased maneuverability by allowing one tractor wheel to turn independently of the other. The Lockout lever on the right handlebar provides instant positive traction when one wheel is spinning in soft soil conditions, on steep slopes, or other problem areas.

The 732 features the same wheel speeds as models 718 and 722, with two forward and reverse speeds and one transport speed in rear-mount "tiller" mode. While the 732's Honda GX340 engine packs plenty of power to handle all mowing applications, the lack of a third, faster working speed limits its mowing productivity.

Differential Drive with Lockout

A fast transport speed to ride your tiller to the garden (requires sulky)

Easy-to-engage, shuttle-type reverse

Anti-vibe handlebars that instantly adjust both vertically and side-to-side

Engine:	Kohler Diesel
Electric Start Option:	Yes
Weight:	289 pounds (with 26" tiller)
Working Speeds:	2 forward, 2 reverse
Working Wheel Speeds:	0.7 and 1.7 MPH
Transport Wheel Speed:	8.3 MPH
Standard Wheel Size:	5" x 10"
Transmission:	All Gear Drive
Clutch Type:	Double Cone, Spring-Loaded
Axle Configuration:	Differential

